

Multiple Banding Machines MB 54 / 74 / 104

For the automatic banding of higher volumes of square-cut labels or similar products, *either inline or off-line*



Multiple Bander			MB 54	MB 74	MB 104
Max. feeding size	LxW	mm	540 x 1040	740 x 1040	1040 x 1040
Max. banding size	LxW	mm	540 x 250	740 x 250	1040 x 250
Min. banding size	LxW	mm	43 x 25	43 x 25	43 x 25
Max. pile height	H	mm	125	125	125
Min. pile height	H	mm	30	30	30
Number of banding stations - optional up to 12 stations			4	4	6
Machine output	strokes/min.		8	8	8
Banding material			polyethylene foil 80µm coated kraft paper 70/30g/m ²		
Width	mm		25 (optional 20, 30 oder 40)		
Machine weight, net	kg		730	810	930

The space-saving Multiple Bander is used for banding rows of paper piles, such as labels, square-cut on a guillotine.

Installation either as a stand-alone machine (e.g. with an air pallet lift) or linked to all known guillotines.

An increased output of the cutting plant is achieved by more effective work flow.

Also applicable for mixed sheets (patented machine system).

With 4-6 banding stations as standard and up to 12 stations as an option, with central adjustment. Banding material is either polyethylene tape or kraft paper tape.

Standard equipment with integrated feed pusher, safety light barrier and clear text display. The machine height is adjustable to achieve a variable height for the working plate. The slope of the roller delivery is also adjustable. All models are available either for delivery to the right or to the left side.



Table Banding Machine TB 24

Maximum output from minimum area

The Busch table banding machine handles difficult work with ease. Suited to different production requirements because of its mobility.



All types of products are banded with coated kraft paper tape (white or brown) or with transparent polypropylene foil tape.

Two sizes are available:
 for 20 and 30 mm tape width
 for 40 and 50 mm tape width
 with an easy adjustment of the tape width.



The banding machines are equipped with adjustable position stops, digital display, error message and electronic temperature control.

Machines can be operated by:

- single stroke release by press-button
- single stroke release by foot pedal
- automatic sensor release

For high volume production a movable large reel stand is offered for reels with 800 m kraft paper tape or 1200 m foil tape.

Large reel stand for TB 24 I and TB 24 II

Max reel diameter	400 mm
Inside diameter of reel core	50 mm
Reel length – kraft paper	800 m / reel
Reel length – PP-foil	1200 m / reel
Tape widths	20, 30, 40, 50 mm
Measurements: (length x width x height)	750 x 500 x 620 – 920 mm
Weight	41 kg

Table Banding Machine

	TB 24 I	TB 24 II
Banding material	coated kraft paper polypropylene foil (PP)	coated kraft paper polypropylene foil (PP)
Tape widths	20 and 30 mm,	40 and 50 mm
Reel length – kraft paper/foil	150 / 200 m	150 / 200 m
Machine output strokes/min	20 – 25	20 – 25
Max. measurements of products to be banded:		
Length	no limit	no limit
Width		
- with kraft paper	240 mm	240 mm
- with foil	180 mm	180 mm
Height	150 mm	150 mm
Machine measurements: (length x width x height)	510 x 320 x 380 mm	510 x 320 x 380 mm
Weight	28 kg	28 kg

