

**Kodak  
Flexcel SRM  
flexographic plates**

**Kodak Flexcel SRM flexographic plates**

**FLEXOGRAPHIC PLATES**

**Technical specifications**

Plate thickness	1.14mm / 0.045", 1.70mm / 0.067", 2.28mm / 0.090", 2.54mm / 0.100", 2.72mm / 0.107 and 2.84mm / 0.112"	
Resolution	1% to 95% @ 150 lpi	
Isolated dot reproduction	100 - 130µm	
Fine line reproduction	70 - 100µm	
Plate hardness Shore A	SRM 1.14mm / 0.045" : 70 SRM 1.70mm / 0.067": 60 SRM 2.28mm / 0.090": 57	SRM 2.54mm / 0.100": 54 SRM 2.72mm / 0.107": 53 SRM 2.84mm / 0.112": 53
Wash-out solution	Compatible with most wash-out solvents Recommended wash-out solvent temperature: 20°C - 35°C (68°F - 95°F)	
Ink compatibility	Aqueous, solvent-based, UV-cured and cationic inks	
Storage and handling	Unopened plate packs should be stored flat and away from excessive cold, heat and humidity. Use in a controlled environment of 10°C - 25°C (50°F - 77°F) and 40 - 55% RH.	

